Appl. No.

: 10/773,560

Filed

: February 5, 2004

## AMENDMENTS TO THE CLAIMS

1. (Cancelled)

- 2. (Cancelled)
- 3. (Cancelled)
- 4. (Cancelled)
- 5. (Cancelled)
- 6. (Cancelled)
- 7. (Withdrawn) The vehicle of Claim 6, wherein the piston actuating movement mechanism comprises at least one piston with an extendable arm wherein the at least one piston is mounted to the slide-out housing such that the arm of the at least one piston can bear against the telescoping member so as to raise and lower the floor of the housing during movement of the slide-out housing.
- 8. (Withdrawn) The vehicle of Claim 1, wherein the piston actuating movement mechanism comprises:

at least one piston mounted to the main housing so as to extend an arm outward away from the main housing;

a pivot point secured to the main housing; and

a movement member coupled to the pivot point and the at least one piston mounted to the main housing such that outward movement of the piston arm results in vertical movement of the movement member so as to exert an upward force on the slide-out housing to thereby move the floor of the slide-out from the third level to the second level and wherein inward movement of the piston arm results in a vertical movement of the movement member so as permit the floor of the slide-out housing to move from the second level to the third level.

- 9. (Withdrawn) The vehicle of Claim 8, wherein the at least one piston comprises two parallel mounted pistons and piston actuated movement mechanism comprises two pivot points with the movement member extending there between.
- 10. (Withdrawn) The vehicle of Claim 9, wherein the movement member includes a member extending between the two pivot points and a roller that is attached to the rotating

'Appl. No. : 10/773,560

Filed: February 5, 2004

members via the arms of the two pistons respectively wherein the arms of the pistons includes a pivot point such that extension of the arms results in upward movement of the roller and retraction of the arms results in downward movement of the roller.

11. (Canceled).

- 12. (Canceled).
- 13. (Currently amended) A recreational vehicle comprising:

a main housing defining an interior living space having a floor located at a first level wherein the main housing defines a first wall having an opening formed therein;

an expandable room having a floor and an outer wall positioned within the opening in the first wall of the main housing, wherein the expandable room is adapted to be movable between a retracted position wherein the floor of the expandable room is positioned at a second level above the first level of the floor of the main housing and the outer wall is positioned substantially adjacent the first wall of the main housing and a deployed position wherein the outer wall is extended away from the first wall of the main housing and the floor of the expandable room is positioned at a third level below the second level so as to be more planar with the first level; and

a piston actuated movement mechanism mounted to the main housing, the piston actuated movement mechanism comprising at least one mounted piston and two pivot points secured to the main housing with a movement member extending between the two pivot points, wherein each of the at least one piston extends a respective arm outward away from the main housing, wherein the respective arm of each of the at least one piston includes a pivot point and wherein the movement member includes a roller that is attached to respective arm of each of the at least one piston such that outward movement of each piston arm results in vertical movement of the roller so as to exert a force having an upward component on the expandable room to thereby move the floor of the expandable room from the third level to the second level and wherein inward movement of each piston arm results in a vertical downward movement of the roller so as to permit the floor of the expandable room to move from the second level to the third level.

a piston actuated movement mechanism mounted to the recreational vehicle, the piston actuated movement mechanism comprising two parallel mounted pistons and two

Appl. No. : 10/773,560

Filed: February 5, 2004

pivot points with a movement member extending between the two pivot points wherein the piston actuated movement mechanism is mounted to the main housing so as to extend an arm outward away from the main housing, a pivot point secured to the main housing, and a movement member coupled to the pivot point and the at least one piston mounted to the main housing such that outward movement of the piston arm results in vertical movement of the movement member so as to exert an upward force on the expandable room to thereby move the floor of the slide out from the third level to the second level and wherein inward movement of the piston arm results in a vertical movement of the movement member so as to permit the floor of the expandable room to move from the second level to the third level wherein the movement member includes a member extending between the two pivot points and a roller that is attached to the rotating members via the arms of the two pistons respectively wherein the arms of the pistons include a pivot point such that extension of the arms results in upward movement of the roller.

- 14. (Original) The vehicle of Claim 13, wherein the third level is co-planar with the first level.
- 15. (Original) The vehicle of Claim 13, further comprising a chassis and a set of wheels to permit rolling movement of the recreational vehicle over the ground.
- 16. (Original) The vehicle of Claim 15, wherein the recreational vehicle comprises a motorhome.
- 17. (Currently amended) The vehicle of Claim 13, further comprising a deployment a and retraction mechanism that moves the expandable room between the first and second retracted and deployed positions.
- 18. (Withdrawn) The vehicle of Claim 17, wherein the deployment and retraction mechanism comprises a housing member that is mounted to the main housing and a telescoping member that is mounted to the expandable room, and wherein the telescoping member outwardly extends from the housing member so as to deploy the expandable room from the main housing, and wherein the telescoping member extends within the housing member so as to retract the expandable room into the main housing.

'Appl. No. :

10/773,560

Filed

.

**February 5, 2004** 

19. (Withdrawn) The vehicle of Claim 18, wherein the piston actuating movement mechanism comprises at least one piston with an extendable arm wherein the at least one piston is mounted to the expandable room such that the arm of the at least one piston can bear against the telescoping member so as to raise and lower the floor of the housing during movement of the expandable room.

- 20. (Cancelled)
- 21. (Cancelled)

Claims 22-34 Canceled.

## 35. (Withdrawn) A recreational vehicle comprising:

a main housing defining an interior living space having a floor located at a first level wherein the main housing defines a first wall having an opening formed therein;

an expandable room having a floor an outer wall positioned within the opening in the first wall of the main housing, wherein the expandable room is adapted to be movable between a retracted position wherein the floor of the expandable room is positioned at a second level above the first level of the floor of the main housing and the outer wall is positioned substantially adjacent the first wall of the main housing and a deployed position wherein the outer wall is extended away from the first wall of the main housing and the floor of the expandable room is positioned at a third level below the second level so as to be more planar with the first level; and

a piston actuated movement mechanism mounted to the recreational vehicle so as to be able to move the side out housing from the second level to the third level when the side-out housing is in the deployed position and move the floor of the expandable room from the third level to the second level when the expandable room is in the retracted position, and wherein the piston actuating movement mechanism comprises at least one piston with an extendable arm wherein the at least one piston is mounted to a portion of the expandable room such that the arm of the at least one piston engages a portion of the main housing so as to raise and lower the floor of the housing during movement of the expandable room.

'Appl. No.

10/773,560

:

**Filed** 

February 5, 2004

36. (Withdrawn) The vehicle of Claim 35, wherein the third level is co-planar with the first level.

- 37. (Withdrawn) The vehicle of Claim 35, further comprising a chassis and a set of wheels to permit rolling movement of the recreational vehicle over the ground.
- 38. (Withdrawn) The vehicle of Claim 37, wherein the recreational vehicle comprises a motorhome.
- 39. (Withdrawn) The vehicle of Claim 35, further comprising a deployment a retraction mechanism that moves the expandable room between the first and second positions.
- 40. (Withdrawn) The vehicle of Claim 39, wherein the deployment and retraction mechanism comprises a housing member that is mounted to the main housing and a telescoping member that is mounted to the expandable room, and wherein the telescoping member outwardly extends from the housing member so as to deploy the expandable room from the main housing, and wherein the telescoping member extends within the housing member so as to retract the expandable room into the main housing.
- 41. (Withdrawn) The vehicle of Claim 40, wherein the piston actuating movement mechanism comprises at least one piston with an extendable arm wherein the at least one piston is mounted to the expandable room such that the arm of the at least one piston can bear against the telescoping member so as to raise and lower the floor of the housing during movement of the expandable room.
- 42. (Withdrawn) The vehicle of Claim 35, wherein the piston actuating movement mechanism comprises:

at least one piston mounted to the main housing so as to extend an arm outward away from the main housing;

a pivot point secured to the main housing; and

a movement member coupled to the pivot point and the at least one piston mounted to the main housing such that outward movement of the piston arm results in vertical movement of the movement member so as to exert an upward force on the expandable room to thereby move the floor of the slide-out from the third level to the second level and wherein inward movement of the piston arm results in a vertical

'Appl. No. :

10/773,560

Filed

: February 5, 2004

movement of the movement member so as permit the floor of the expandable room to move from the second level to the third level.

- 43. (Withdrawn) The vehicle of Claim 42, wherein the at least one piston comprises two parallel mounted pistons and piston actuated movement mechanism comprises two pivot points with the movement member extending there between.
- 44. (Withdrawn) The vehicle of Claim 43, wherein the movement member includes a member extending between the two pivot points and a roller that is attached to the rotating members via the arms of the two pistons respectively wherein the arms of the pistons includes a pivot point such that extension of the arms results in upward movement of the roller and retraction of the arms results in downward movement of the roller.
  - 45. (Canceled).
  - 46. (Canceled).
- 47. (Currently amended) A method of moving a slide-out assembly of a recreational vehicle, the method comprising:

positioning a slide-out room within the main housing of a recreational vehicle such that the floor of the slide-out room is positioned at a first level above the floor of the main housing and such that an outer wall of the slide-out room is positioned proximate to the outer wall of the main housing;

deploying the slide-out room into a deployed position wherein the outer wall of the slide-out room is positioned distally from the outer wall of the main housing to thereby increase the floor space of the recreational vehicle;

lowering the floor of the slide-out room from the first level to a second level which is more proximate the a level of the floor of the main housing;

retracting the slide-out room such that the outer wall of the slide-out room is proximate the outer wall of the main housing; and

moving a piston member such that the an arm of the piston member moves the floor of the slide-out room from the second level to the first level when the slide-out room is retracted wherein moving the piston member comprises extending or retracting a the piston member outward or inward from the main housing so as to engage a linkage member of a roller assembly that respectively rises or lowers to engage the slide-out to

Appl. No.

: 10/773,560

Filed

: February 5, 2004

thereby move the floor of the slide-out up to the first level during retraction of the slide-out room and downward to the second level during deployment of the slide-out room.

- 48. (Original) The method of Claim 47, wherein lowering the floor of the slide-out room from the first level to the second level comprises moving the floor of the slide-out room from a level above the floor of the main level in the retracted position to a level that is substantially co-planar with the floor of the main section of the housing.
  - 49. (Cancelled)
- 50. (Currently amended) The method of Claim 47, wherein moving the piston member comprises extending a-the piston member coupled between the slide-out room and the main level housing so as to raise the floor of the slide-out from the second level to the first level as the slide-out is being retracted.
- 51. (Original) The method of Claim 50, wherein extending a piston member comprises extending an arm of a piston mounted to the main housing so as to engage the slide-out room while the slide-out room is being retracted to thereby move the slide-out room from the second level to the first level.
- 52. (Original) The method of Claim 47, wherein extending a piston member comprises extending an arm of a piston mounted to the slide-out room so as to engage a portion of the recreational vehicle to thereby lift the slide-out room from the second level to the first level as the slide-out room is being retracted.
  - 53. (Cancelled)